

Aves 0W-16

Performance Claims

SAE 0W-16
API SP/SN Plus

ILSAC GF-5/-6B, Ford, GM, Chrysler, Toyota, Lexus, KIA, Honda,
Nissan, Mitsubishi, Subaru, Suzuki



Description

High-performance fully synthetic engine oil specially developed for American and Asian petrol engines of passenger cars, delivery vans, and hybrids. Minimizes the risk of Low-Speed Pre-Ignition in modern engines with GDI and TGDI. Ensures excellent low-temperature flow characteristics to provide optimum protection for the engine at the cold start phase. Withstands extreme loads and safely handles high temperatures under all operating conditions.

Advantages

- **Optimal engine protection:** Protects against wear, sludge, and corrosion.
- **Enhanced fuel efficiency:** Reduces fuel consumption.
- **Superior cold-start performance:** Ensures quick and reliable starts in cold weather.
- **Extended engine life:** Prolongs engine life with superior wear protection.
- **Formulated for modern engines:** Compatible with a wide range of gasoline engines.

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20 °C	ASTM D1298	kg/m ³	870
Viscosity at -35 °C	ASTM D5293	cP	6200
Viscosity at 100 °C	ASTM D445	cSt	7,1
Viscosity index	ASTM D2270		140
Flash point COC	ASTM D92	°C	200
Pour point	ASTM D97	°C	-40
TBN	ASTM D4739	mgKOH/g	5,0
Sulphate ashes	ASTM D874	%	1,0

Packaging

VOLUME	ART N ^o
5 L	0196
5 L (Tin can)	0175