

Aves 0W-40

Performance Claims

SAE 0W-40
API SN/CF
ACEA A3/B4

BMW Longlife-01 MB 229.3 VW 502.00 VW 505.00



Description

High-performance HC-Synthetic multigrade fuel-economy oil for diesel and petrol car engines. Specially selected HC-Synthetic base oils and highly effective long-term protective additives give this high-performance motor oil its excellent driving characteristics. The fuel economy leads to a reduction in CO2 emissions.

Advantages

- High wear protection at all operating conditions
- Excellent viscosity-temperature behavior
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20°C	ASTM D1298	kg/m ³	900
Viscosity at -35°C	ASTM D5293	cP	6200
Viscosity at 100°C	ASTM D445	cSt	13,5
Viscosity index	ASTM D2270		130
Flash point COC	ASTM D92	°C	180
Pour point	ASTM D97	°C	-30
TBN	ASTM D4739	mgKOH/g	5,5
Sulphate ashes	ASTM D874	%	1,5

Packaging

VOLUME	ART №
5 L	0091
5 L (Tin can)	0158
200 L	0092