

## Aves C3 5W-30

### Performance Claims

SAE 5W-30  
API SN/CF  
ACEA C3

VW NORM 504.00/507.00;  
MB 229.51; PORSCHE C30;  
BMW Longlife-04



### Description

Multipurpose fuel efficient synthetic engine oil for passenger cars and vans. Designed for the most advanced petrol and diesel engines with and without turbocharging. Suitable for the diesel engines equipped with a pump dose and a diesel particulate filter (ACEA C3).

### Advantages

- Excellent engine cleanliness and performance
- Reduces fuel consumption
- Extended oil drain intervals (Longlife) DPF and ERG system longlife due to low-ash formula
- Highest performance over the full temperature range

### Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	855
Viscosity at -30°C	ASTM D5293	cP	5640
Viscosity at 40°C	ASTM D445	cSt	64,0
Viscosity at 100°C	ASTM D445	cSt	11,5
Viscosity index	ASTM D2270		176
Flash point COC	ASTM D92	°C	230
Pour point	ASTM D97	°C	-45
TBN	ASTM D4739	mgKOH/g	6,7
Sulphate ashes	ASTM D874	%	0,67

### Packaging

VOLUME	ART No
1 L	0004
4 L	0005

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.