

# Aves RC 0W-20

## Performance Claims

SAE 0W-20  
API SP (RC)

MB 229.72, Jaguar Land Rover STJLR.03.5006, GM DEXOS 1 GEN 2, GM 6094M, Ford WSS-M2C947-A, Ford WSS-M2C947-B1, Ford WSS-M2C962-A1, BMW Longlife-17 FE+, Opel / Vauxhall OV0401547, Volvo VCC RBS0-2AE, Fiat 9.55535-GSX, Chrysler MS-12145



## Description

NORDKAPP AVES RC SAE 0W-20 is a fully synthetic low-friction engine oil of the latest generation. The exceptional qualities fulfill modern OEM requirements and application conditions. It is optimally coordinated for prolonged oil change intervals.

NORDKAPP AVES RC SAE 0W-20 is especially suitable for use in passenger petrol and diesel engines with subsequent exhaust treatment systems (DPF), which require engine oils with a low viscosity according to the OEM manual. The newest formula protects the engine as well as the catalytic converter system.

## Advantages

- Guarantee efficient lubrication of the engine.
- High fuel economy effect.
- Ensures protection against sludging, coking, varnish, and corrosion even under unfavorable operating conditions.
- Optimal energy saving and lifetime properties.
- Neutral towards sealing materials.
- Excellent low-temperature, anti-friction, anti-corrosion, detergent, and antioxidant characteristics.

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20°C	ASTM D1298	kg/m <sup>3</sup>	870
Viscosity at -35°C	ASTM D5293	cP	6200
Viscosity at 100°C	ASTM D445	cSt	7,45
Viscosity index	ASTM D2270		140
Flash point COC	ASTM D92	°C	200
Pour point	ASTM D97	°C	-42
TBN	ASTM D4739	mgKOH/g	5,0
Sulphate ashes	ASTM D874	%	1,5

## Packaging

VOLUME	ART №
5 L	0198
5 L (Tin can)	0210